

## SPECIFICATIONS

### MODEL

UMC425

---

### VERSATOOL COMPATIBLE

Yes

---

### TYPE

4-stroke, overhead cam, single-cylinder, horizontal shaft

---

### BORE & STROKE

35 x 26 mm (1.4 x 1.0 in)

---

### DISPLACEMENT

25cm<sup>3</sup> (1.5 cu in)

---

### COMPRESSION RATIO

8.0:1

---

### NET POWER

0.72kW (1.0HP) at 7,000 rpm

---

### MAXIMUM NET TORQUE

1.0 Nm (0.74 lbs ft) at 5,000 rpm

---

### IGNITION SYSTEM

Transistorised magneto ignition

---

### STARTING SYSTEM

Recoil Starter

---

### COOLING SYSTEM

Forced-air

---

### PTO SHAFT ROTATION

Counter-clockwise (from P.T.O. side)

---

### FUEL CONSUMPTION AT RATED POWER

0.54 L/h at 7,000 rpm

---

---

**RECOMMENDED FUEL**

Unleaded

---

**LUBRICATION SYSTEM**

Oil Mist

---

**OIL CAPACITY**

0.08l

---

**FUEL TANK CAPACITY**

0.55l

---

**DIMENSIONS**

192mm x 221mm x 230mm

---

**DRY WEIGHT**

2.78kg (w/o clutch)

---

**OTHER SPECS**

Infinite Operating Angles

---