

## SPECIFICATIONS

### MODEL

UMC435

---

### VERSATOOL COMPATIBLE

Yes

---

### TYPE

4-stroke, overhead cam, single-cylinder, horizontal shaft

---

### BORE & STROKE

39 x 30 mm (1.5 x 1.2 in)

---

### DISPLACEMENT

35.8cm<sup>3</sup> (2.2 cu in)

---

### COMPRESSION RATIO

8.0:1

---

### NET POWER

1.0kW (1.3HP) at 7,000 rpm

---

### MAXIMUM NET TORQUE

1.6 Nm (1.2 lbs ft) at 5,500 rpm

---

### IGNITION SYSTEM

Transistorised magneto ignition

---

### STARTING SYSTEM

Recoil Starter

---

### COOLING SYSTEM

Forced-air

---

### PTO SHAFT ROTATION

Counter-clockwise (from P.T.O. side)

---

### FUEL CONSUMPTION AT RATED POWER

0.71 L/h at 7,000 rpm

---

---

**RECOMMENDED FUEL**

Unleaded

---

**LUBRICATION SYSTEM**

Oil Mist

---

**OIL CAPACITY**

0.1l

---

**FUEL TANK CAPACITY**

0.65l

---

**DIMENSIONS**

198mm x 234mm x 240mm

---

**DRY WEIGHT**

3.33 kg (w/o clutch)

---

**OTHER SPECS**

Infinite Operating Angles

---