

# RIDE-ON MOWERS & ZERO TURNS 2018-2019

^Credit approved applicants only. Fees, terms and conditions apply. See page back page for full details.



VICTA.COM.AU

# VICTA ZAPA

## THE EASY CHOICE.



**VRX Ride-On** Page 6



**SPX™ Ride-On** Page 8



**ZTX Mowers** Page 10



Accessories Page 12

# EASY TO USE. EASY TO OWN.

With the largest range of Ride-On mowers in Australia, Victa°'s range of Ride-On mowers and zero turn mowers are specially designed to help you comfortably and easily mow your acreage faster! Speak to an expert today to learn which Victa model best suits your needs.

### **WHY CHOOSE A VICTA DEALER?**



1. EXPERT SERVICE AND ADVICE
You will always be in good hands at your local Victa Dealer. Your resident dealer is your local expert for all things mower sales, parts and service.



3. HASSLE-FREE PURCHASE
At a Victa Dealer, you will be up and
running in no time! Your dealer is able to
assist with set-up and delivery of your
new mower.



2. TEST DRIVE
Your local dealer can arrange a test
drive and provide operator and safety
demonstrations.



### 4. SERVICE SUPPORT

To maximise the performance of your Victa mower, Victa Dealers stock a huge range of genuine parts and accessories. All work is completed by factory-trained service technicians using customised tooling.



Your local Victa® Dealer employs trained and qualified Master Service Technicians. Using only genuine parts, your Victa Dealer can ensure the highest quality service, every time.







4 | victa.com.au | 5

### **VRX RIDE-ON**



### **Tried and True**

Some dependable designs are ingeniously simple. The Peerless<sup>®</sup> manual transmission or Hydro-Gear® T2-HP™ hydrostatic transmission offer smooth reliable operation.



### **Stamped Steel Mower Deck**

Stamped out of durable rolled steel and designed to create a powerful amount of airflow for the disposal of a large amount



### Mulch Plug

Finely mulch your grass using the mulch plug included as standard. While the blade mulches the grass clippings, the deck design blows them back into the lawn



### **Getting Started**

Briggs & Stratton® Engines offer the reliability you can count on when mowing the lawn.



Feature packed Victa® VRX - Rear Catcher is the ideal mower for homeowners after a perfectly neat finish. Featuring an easy to use catcher system, your lawn is sure to be the envy of your neighbours.

### VRX15538GX 38" Stamped Deck 15.5 Gross HP\*

500 cc Briggs & Stratton Intek™ Series OHV Engine

Gear Drive Transmission

2 Year Limited Warranty'

### VRX15538H

38" Stamped Deck 15.5 Gross HP\*

500 cc Briggs & Stratton Intek™ Series OHV Engine

Hydro-Gear® T2-HP™ Hydrostatic

2 Year Limited Warranty'

### VRX19542H

42" Stamped Deck 19 Gross HP\*

500 cc Briggs & Stratton Intek™ Series OHV Engine

Hydro-Gear® T2-HP™ Hydrostatic

2 Year Limited Warranty

### VRX17533HC

33" Stamped Deck 17.5 Gross HP\*

500 cc Briggs & Stratton Intek™ Series OHV Engine

Hydro-Gear® T2-HP® Hydrostatic

210 Litre Rear Catching 2 Year Limited Warranty



# **QUALITY FEATURES.** AFFORDABLE PRICES.

### **SPX™ SERIES**



Step Up to High Value

All-steel construction including the bonnet, cast-iron front axle and a hydrostatic transmission are hallmarks of premium tractors - all at a value price.



Quick-Adjust Cutting Height

Easy-to-use height-of-cut controls adjust the mower deck for changing grass conditions.



**Fabricated Mower Decks** 

The durable 42" and 48" fabricated mower decks feature welded, heavy-duty steel for non-stop mowing season-after season. All fabricated decks come with a limited lifetime warranty'.



Step On It

Our responsive foot pedals give you hands-free control over forward and reverse speed. The dash-mounted cruise control lets you set your speed.



**Turning Perfection** 

With a 14" turning radius, you can spend less time mowing and more time enjoying your yard.



A Generation of Power

Briggs & Stratton Professional Series™ V-Twin OHV Engines have full-pressure lubrication and spin-on oil filters for

### **SPX**<sup>™</sup> 2342 42" Stamped Deck 23 Gross HP

724 cc Briggs & Stratton Professional Series™ V-Twin OHV Engine

Hydro-Gear® T2-HP™ Hydrostatic

42" Stamped Steel Deck

3 Year\*\* Limited Warranty

### SPX<sup>™</sup> 2342F

42" Fabricated Deck 23 Gross HP\*

724 cc Briggs & Stratton Professional Series™ V-Twin OHV Engine

Hydro-Gear® T2-HP™ Hydrostatic

42" Fabricated Deck - Limited Lifetime Warranty

3 Year\*\* Limited Warranty

### **SPX**<sup>™</sup> 2348F

48" Fabricated Deck 23 Gross HP\*

724 cc Briggs & Stratton Professional Series<sup>™</sup> V-Twin OHV Engine

Hydro-Gear® T2-HP™ Hydrostatic

48" Fabricated Deck - Limited Lifetime Warranty

3 Year\*\* Limited Warranty

### \*All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton. \*See operator's manual or dealer for complete warranty details. \*\*Extended warranty available see dealer for details.

# STRAIGHTFORWARD DESIGN.



### **ZTX ZERO TURN**





### Commercially-Inspired

A fully-welded steel frame, thick-walled front axle, durable mower deck, and ball bearings in the caster spindles ensure durability and a great cut.



### Dependable Power

High performance Briggs & Stratton Professional Series<sup>™</sup> engine with ReadyStart°, making sure your zero turn mower has the power to perform year



### **Heavy-Duty Mower Decks**

A durable fabricated steel mower deck provides non-stop mowing season after season, and comes with a **limited lifetime** 

42 and 48" decks only



### More Than Just a Zero Turn

Victa°'s first dirt-hauling, tool-toting, flower-delivering and, of course, grass-cutting zero turn mower. The integrated cargo bed' provides on-the-go versatility and convenience. Plus, the rail system is compatible with numerous third-party UTV/ATV accessories for added utility around



The Choice is Yours

The commercial-style foot-operated mower deck lift easily lifts and adjusts the mower deck between 13 height-of-cut positions from 3.8 to 11.4cm (1.5 - 4.5").

### your yard.

**ZTX 2342F** 42" Fabricated Deck

724 cc Briggs & Stratton Professional Series™ V-Twin OHV Engine

Hydro-Gear® EZT® Hydrostatic Transaxles

Optional Cargo Bed<sup>†</sup> Fabricated Deck - Limited Lifetime

3 Year\*\* Limited Warranty

### **ZTX 2246**

46" Stamped Deck 22 Gross HP\*

724 cc Briggs & Stratton Intek Series™ V-Twin OHV Engine

Hydro-Gear® EZT® Hydrostatic Transaxles

Optional Cargo Bed<sup>†</sup>

46" Stamped Steel Deck

3 Year\*\* Limited Warranty'

### **ZTX 2348F**

48" Fabricated Deck 23 Gross HP\*

724 cc Briggs & Stratton Professional Series™ V-Twin OHV Engine

Hydro-Gear® EZT® Hydrostatic Transaxles

Optional Cargo Bed<sup>†</sup>

Fabricated Deck - Limited Lifetime Warranty<sup>†</sup>

3 Year\*\* Limited Warranty\*

# **NEW LEVELS** OF VERSATILITY.



Warranty'

### IT'S EASY TO GET ATTACHED.

Victa® accessories take your mower to the next level by adding even more options to make mowing even easier.

### Accessories



Trailer Hitch Allows you to quickly and easily attach a trailer to your Victa Ride. Fits VRX (Standard)



**Grass Mulcher Kit** Reduce your number of clippings by finely mulching them back into the lawn. Fits SPX™ and ZTX Standard on VRX



Provides you comfortable shade while you mow.



Clean Sweep™ Twin Collector Roomy enough for 228 litres of clippings in two easy-to-empty bags.



Swing Back Blade Kit Easily convert your cutting system to swing back blades using the oval disc and blade kit Fits 42 inch SPX™ and ZTX

Note: Attachments for prior year models and additional attachments or accessories not shown may be available. Some attachments require additional installation components (i.e. front weights for a catcher). Please see dealer for details.



**SPECIFICATIONS** 

Broad   Broa	Model	VRX15538GX	VRX15538H	VRX19542H	VRX17533HC	SPX <sup>™</sup> 2342	SPX <sup>™</sup> 2342F	SPX <sup>™</sup> 2348F
Branch	Engine							
Cylinder's   Chip   C	Brand	""				Professional Series <sup>™</sup>	Professional Series <sup>™</sup>	Professional Series™
Chair   Manual Chairs   Manual Chairs   Manual Chairs   Manual Chairs   Manual Chairs   Chairs   Manual Chairs   Chairs   Matter   Chair	· ·	15.5 / 1	15.5 / 1	19 / 1	17.5 / 1	23 / 2	23 / 2	23 / 2
Electric with Key Stort   Electric with Ke	Engine Displacement (cc)	500	500	500	500	724	724	724
Tendination	Choke / Throttle	Manual Choke	Manual Choke	Manual Choke	Manual Choke	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic
Cutres   0	Start Type	Electric with Key Start	Electric with Key Start	Electric with Key Start				
Transmission Make	1 1	6	6	6	6	13.3	13.3	13.3
Differential   Gear Drive   Nydro	Transmission							
Speed Control Design	Transmission Make	Peerless*	Hydro-Gear <sup>®</sup>	Hydro-Gear°	Hydro-Gear°	Hydro-Gear°	Hydro-Gear <sup>®</sup>	Hydro-Gear <sup>®</sup>
Property	Differential	Gear Drive	Hydro	Hydro	Hydro	Hydro	Hydro	Hydro
Company   Comp	Speed Control Design	Gear Shift Lever	Foot Pedals	Foot Pedals	Foot Pedals	Foot Pedals	Foot Pedals	Foot Pedals
Promat   10-Gouge Steel   10-Gouge Ste	·	7.3 / 4.5	7.3 / 4.5	7.3 / 4.5	7.3 / 4.5	9/5.5	9 / 5.5	9/5.5
Front Asle		Disc	Disc	Disc	Disc	Disc	Disc	Disc
Front Axle	Frame	10-Gauge Steel	10-Gauge Steel	10-Gauge Steel	10-Gauge Steel	12-Gauge Steel	12-Gauge Steel	10 Gauge Fabricated
Turning Radius         42 cm (16.5°)         42 cm (16.5°)         42 cm (16.5°)         35 cm (14°)         35 cm (14°)         35 cm (14°)           Front Tyres (inches)         13 x 5 - 6         15 x 6 - 6	Front Axle	-	Welded Steel	Welded Steel	Welded Steel			
Rear Tyres (Inches)	Turning Radius	42 cm (16.5")	42 cm (16.5")	42 cm (16.5")	42 cm (16.5")	35 cm (14")	35 cm (14")	35 cm (14")
Seat   Mid back, adjustable   Mid back, adjustable   Mid back, adjustable   Low back, adjustable   High-back, adjustable   High-back, adjustable   High-back, adjustable   Mower Deck	Front Tyres (inches)	13 x 5 - 6	15 x 6 - 6	15 x 6 - 6	15 x 6 - 6			
Deck Type	Rear Tyres (inches)	18 x 8.50 - 8	20 x 10 - 8	20 x 10 - 8	20 x 10 - 8			
Deck Type	Seat	Mid back, adjustable	Mid back, adjustable	Mid back, adjustable	Low back, adjustable	High-back, adjustable	High-back, adjustable	High-back, adjustable
Cutting Width (inches)         38         38         42         33         42         42         48           Mower Configuration         Side Discharge	Mower Deck							
Mower Configuration   Side Discharge   Number of Blades   2   2   2   2   2   2   3	Deck Type	Stamped Steel	Fabricated Steel	Fabricated Steel				
Number of Blades   2	Cutting Width (inches)	38	38	42	33	42	42	48
Height-of-Cut Range (Indicative)   2.5 cm - 8 cm (1" - 3.1")   3.8 cm - 10 cm (1.5" - 4")   3.8 cm - 10	Mower Configuration	Side Discharge	Side Discharge	Side Discharge	Rear Catch	Side Discharge	Side Discharge	Side Discharge
Control   No   No   No   No   No   No   Yes	Number of Blades	2	2	2	2	2	2	3
Blade Engagement Electric PTO Switch Manual Ma		2.5 cm - 8 cm (1" - 3.1")	2.5 cm - 8 cm (1" - 3.1")	2.5 cm - 8 cm (1" - 3.1")	2.5 cm - 8 cm (1" - 3.1")	3.8 cm - 10 cm (1.5" - 4")	3.8 cm - 10 cm (1.5" - 4")	3.8 cm - 10 cm (1.5" - 4")
Mower Deck Lift         Manual         Manual <t< th=""><th>Height-of-Cut Positions</th><th>7</th><th>7</th><th>7</th><th>7</th><th>7</th><th>7</th><th>7</th></t<>	Height-of-Cut Positions	7	7	7	7	7	7	7
Features	Blade Engagement	Electric PTO Switch	Electric PTO Switch	Electric PTO Switch				
Cruise Control         No         No         No         No         Yes         Yes         Yes           Headlights         Yes         Yes         Yes         Yes         Yes         Yes           Fuel Level Indicator         Translucent Tank         Translucent Tank         Translucent Tank         Translucent Tank         Translucent Tank         Translucent Tank           Dimensions         Length x Width x Height (cm)         173 x 120 x 107         173 x 120 x 107         173 x 132 x 107         243 x 90 x 107         180 x 117 x 107         180 x 150 x 107         180 x 165 x 107	Mower Deck Lift	Manual	Manual	Manual	Manual	Manual	Manual	Manual
Headlights Yes Yes Yes Yes Yes Yes Yes Yes Yes Ye	Features							
Fuel Level Indicator         Translucent Tank         Tank<	Cruise Control	No	No	No	No	Yes	Yes	Yes
Dimensions         Length x Width x Height (cm)         173 x 120 x 107         173 x 120 x 107         173 x 132 x 107         243 x 90 x 107         180 x 117 x 107         180 x 150 x 107         180 x 165 x 107           Domestic Limited Warranty'	Headlights	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Length x Width x Height (cm)         173 x 120 x 107         173 x 120 x 107         173 x 132 x 107         243 x 90 x 107         180 x 117 x 107         180 x 150 x 107         180 x 165 x 107           Domestic Limited Warranty'         Warranty'         180 x 150 x 107         180 x 165 x 107         180 x 1	Fuel Level Indicator	Translucent Tank	Translucent Tank	Translucent Tank				
(cm) 1/3 x 120 x 107 1/3 x 120 x 107 1/3 x 132 x 107 243 x 90 x 107 180 x 117 x 107 180 x 150 x 107 180 x 165 x 107  Domestic Limited Warranty'	Dimensions							
Warranty'		173 x 120 x 107	173 x 120 x 107	173 x 132 x 107	243 x 90 x 107	180 x 117 x 107	180 x 150 x 107	180 x 165 x 107
Engine   2 Year   2								
	Engine	2 Year	2 Year	2 Year	2 Year	2 Year"	2 Year"	2 Year"
Mower Deck   2 Year   Limited Lifetime   Limited Lifetime	Mower Deck	2 Year	2 Year	2 Year	2 Year	2 Year"	Limited Lifetime	Limited Lifetime
Balance of Mower 2 Year 2 Year 2 Year 2 Year 3 Year" 3 Year" 3 Year"	Balance of Mower	2 Year	2 Year	2 Year	2 Year	3 Year**	3 Year"	3 Year"

Model	ZTX 2342F	ZTX 2246	ZTX 2348F
Engine			
Brand	Briggs & Stratton Professional Series <sup>™</sup> V-Twin OHV	Briggs & Stratton Intek™ Series™ V-Twin OHV	Briggs & Stratton Professional Series <sup>™</sup> V-Twin OHV
Gross Horsepower* / Cylinders	23 / 2	22 / 2	23 / 2
Engine Displacement (cc)	724	724	724
Choke / Throttle	Choke-a-Matic	Choke-a-Matic	Choke-a-Matic
Start Type	Electric with Key Start	Electric with Key Start	Electric with Key Start
Fuel Tank Capacity (Litres)	11.4	11.4	11.4
Transaxles			
Transaxle Make	Dual Hydro-Gear® EZT®	Dual Hydro-Gear® EZT®	Dual Hydro-Gear® EZT®
Differential	Hydro	Hydro	Hydro
Speed- Fwd / Rev. (km/h)	11.2 / 6.4	9.6 / 4.8	11.2 / 6.4
Brake	Integrated	Integrated	Integrated
Chassis			
Frame	12-Gauge Welded	12-Gauge Welded	12-Gauge Welded
Front Axle	Welded Steel, Fixed	Welded Steel, Fixed	Welded Steel, Fixed
Front Tyres (inches)	11 x 4	11 x 4	11 x 4
Rear Tyres (inches)	20 x 8	18 x 8.50	20 x 8
Number of Anti-Scalp Wheels	1 Front, 1 Rear	1 Front, 1 Rear	2 Front
Seat	Mid-Back, adjustable	Mid-Back, adjustable	Mid-Back, adjustable
Mower Deck			
Deck Type	Fabricated Steel	Stamped Steel	Fabricated Steel
7.0			
Cutting Width (inches)	42	46	48
	42 Side Discharge	46 Side Discharge	48 Side Discharge
Cutting Width (inches)			-
Cutting Width (inches)  Mower Configuration	Side Discharge	Side Discharge	Side Discharge
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range	Side Discharge	Side Discharge	Side Discharge
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)	Side Discharge 2 3.8 - 11.4cm (1.5 - 4.5")	Side Discharge 3 3.8 - 11.4cm (1.5 - 4.5")	Side Discharge 3 3.8 - 11.4cm (1.5 - 4.5")
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")	Side Discharge 3 3.8 - 11.4cm (1.5 - 4.5")
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features  Rear Bumper  Hour Meter  Cup Holder	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features  Rear Bumper  Hour Meter	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (Indicative) Height-of-Cut Positions Blade Engagement Mower Deck Lift Features Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (Indicative) Height-of-Cut Positions Blade Engagement Mower Deck Lift Features Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Cargo Bed	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (Indicative) Height-of-Cut Positions Blade Engagement Mower Deck Lift Features Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Cargo Bed Dimensions	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes
Cutting Width (inches) Mower Configuration Number of Blades Height-of-Cut Range (Indicative) Height-of-Cut Positions Blade Engagement Mower Deck Lift Features Rear Bumper Hour Meter Cup Holder Fuel Level Indicator Armrest Cargo Bed Dimensions Length x Width x Height (cm)	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features  Rear Bumper  Hour Meter  Cup Holder  Fuel Level Indicator  Armrest  Cargo Bed  Dimensions  Length x Width x Height	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Yes  Optional	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes Optional	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes Optional
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features  Rear Bumper  Hour Meter  Cup Holder  Fuel Level Indicator  Armrest  Cargo Bed  Dimensions  Length x Width x Height (cm)	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Yes  Optional	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes Optional	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch Foot Operated  Yes Yes Yes Yes Yes Optional
Cutting Width (inches)  Mower Configuration  Number of Blades  Height-of-Cut Range (Indicative)  Height-of-Cut Positions  Blade Engagement  Mower Deck Lift  Features  Rear Bumper  Hour Meter  Cup Holder  Fuel Level Indicator  Armrest  Cargo Bed  Dimensions  Length x Width x Height (cm)  Domestic Limited  Warranty'	Side Discharge  2  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Optional  183 x 140 x 107	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Optional  183 x 150 x 107	Side Discharge  3  3.8 - 11.4cm (1.5 - 4.5")  13  Electric PTO Switch  Foot Operated  Yes  Yes  Yes  Yes  Optional  183 x 150 x 107

# SEE THE FULL RANGE OF VICTA® PRODUCTS AT VICTA.COM.AU



### SPEAK TO YOUR DEALER ABOUT BRIGGS & STRATTON'S POWER PRODUCTS







### **Briggs & Stratton Australia Pty Ltd**

**PO BOX 84** 

Moorebank NSW 1875

P: 1800 356 632

©2018 ALL RIGHTS RESERVED

Product specifications and colours are subject to change without prior notification.

Hydro-Gear® is a trademark of Hydro-Gear Inc. and is used under license.

Briggs & Stratton: All power levels are stated gross horsepower at 3600rpm per SAE J1940 as rated by Briggs & Stratton.

^Approved applicants only. Fees, terms, conditions & minimum finance amount (\$800) apply, incl \$99 Annual Fee charged on the account open date and annually on the anniversary of that date. Annual Fee must be paid in full within 90 days or it will attract interest. Minimum monthly repayment required. Interest, (charged at the Expired Promotional Rate) payable on outstanding balances after any Interest Free Period. See skyecard.com.au for current interest rates. Only available at Skye retail partners. Credit provided by FlexiCards Australia Pty Ltd ABN 31 099 651 877 Australian Credit Licence number 247415. FlexiCards Australia is a subsidiary of FlexiGroup Limited.

